



Rijksweg 33a
NL - 6584 AA Molenhoek (Ib)
The Netherlands

T +31 (0)24 - 3977590
F +31 (0)24 - 3972856
E info@lhpackaging.nl

LH PACKAGING BV

[Http://www.lhpackaging.nl](http://www.lhpackaging.nl)

Blend of traditional and innovative modern design, is the market demand, combined with technology, especially the world's leading research and development.
Radian beautiful, elegant curves, simple style with full details of Continental grade;



Flexible tube Automatic filling and sealing machine

Automatic Flexible Tube Filling and Sealing Machine is suitable for filling all kinds of pasty and viscous fluid and the materials alike, into plastic and composite metal tubes and then internally heating tubes, sealing and printing lot number. It is used in the industries of pharmaceuticals, foodstuffs, cosmetic and daily chemicals. The control parts of the machine are composed of intelligent Man-computer interface, SIEMENS large touch screen display, SIEMENS PLC control panel, including temperature setting, motor speed, filling speed, direct screen display, screen display and screen control. The components of the machine which touched the filling material are made of stainless steel SUS304 and SUS316L. Transparent cover, feeding device also supplied with the machine. The machine is featured with safety switch, auto-stop, process of hose-feeding and setting, filling and sealing, the ejecting are all automatically controlled. Digital count device is the filling head is put inside the material, blow-off device is installed to ensure a complete sealing. Many choices of sealing type are available to meet your different requirements.

Your different requirement is available



Water Chiller



Automatic Feeding Machine

Technical parameter

| | |
|-------------------------|---------------------------------|
| Voltage | AC 220V/50HZ ± 10%. |
| Heating power | Main is 3KW (electric heating). |
| Motor power | 1.1KW |
| Filling volume | 5-250ml(tube) |
| Filling accuracy | ≤1% |
| Capacity | 1800-2400(tubes /h Adjustable) |
| Tube diameter | 10-50mm |
| Tube length | 210mm (Max. Length) |
| Hopper volume | 40 L |
| Compressed Air pressure | 0.6Mpa/ square centimeters |
| Dimension (L×W×H) | 1900×1000×1950mm |
| Weight: (Approx) | 900kgs |



Filling and sealing samples