

LH-Series Powder Automatic Vertical Packaging Machine

LH PACKAGING BV  
http://www.lhpackaging.nl



Technical parameter

Model	LH-320AP	LH-420AP	LH-520AP	LH-680AP	LH-820AP
Packaging material	OPP/CPP OPP/CE PET/PE etc.composite film				
Bag length	50-200mm(L)	300mm(L)	400mm(L)	400mm(L)	500mm(L)
Bag width	50-150mm(W)	100-200mm(W)	150-250mm(W)	180-320mm(W)	250-400mm(W)
Film width	320mm	420mm	520mm	680mm	820mm
Packing speed	8-60bags/min	5-60bags/min	5-60bags/min	5-50bags/min	5-50bags/min
Range of measurement	20-500ml	2500ml	6000ml	10L	15L
Atmospheric pressure	0.65Mpa	0.65Mpa	0.65Mpa	0.65Mpa	0.65Mpa
Consumption	0.6m³/min	0.6m³/min	0.7m³/min	0.8m³/min	0.8m³/min
Voltage	220V 50/60Hz	220V 50/60Hz	220V 50/60Hz	220V 50/60Hz	220V 50/60Hz
Power	1.5Kw	3.0Kw	4.0Kw	5.0Kw	5.0Kw
Dimensions	L1067*W1026*H1288mm	L1388*W116*H1536mm	L1795*W1150*1650mm	L1480*W1380*H1850mm	L1600*W1530*H2100mm
Weight	300Kg	500Kg	600Kg	700Kg	850Kg

LH PACKAGING BV

Rijksweg 33a  
NL - 6584 AA Molenhoek (lb)  
The Netherlands  
T +31 (0)24 - 3977590    F +31 (0)24 - 3972856  
H www.lhpackaging.nl    E info@lhpackaging.nl



Automatic Powder Packaging Machine



Automatic Liquid And Paste Packaging Machine



Automatic Granule Packaging Machine



LARGE MATERIAL ELEVATOR



LARGE FINISHED PRODUCT CONVEYOR




SCREW ELEVATOR



TRUNK STYLE FORMER

Technical parameter

Model	LH-280P	LH-280L
Bag-making length	50-150mm	50-150mm
Bag-making width	40-130mm	40-130mm
Packing film width	80-280mm	80-280mm
Packing capacity	3-30 / 30-100 grams	3-30 / 30-100 grams
Packing speed	30-60 bags/minute	30-60 bags/minute
Power	2.0kw	2.5kw
Air Power	0.6-0.8Mpa	0.6-0.8Mpa
Overall Dimension	830*700*1580mm	830*700*1580mm
Weight	300kg	300kg




①



②



③



④

Packaging styles

Combined parts

- 1、LH series vertical machine
- 2、Vibration feeder
- 3、10/14 heads weigher
- 4、Supporting platform
- 5、Z type bucket elevator
- 6、Product conveyor

Main performance & characteristics

- 1. Standard with computer-controlled multi-head weight (10、14、16 head), which has a high-precision, high-speed and good man-machine interface. Easy to operate and clean.
- 2. It is widely used in food industry for packing irregular and uneven weight products.
- 3. Less manpower, less waste, easy operation and maintenance.
- 4. It can finish automatically all processes, from measuring, filling, bag making, date stamp and finished goods conveyance.



CSAR STYLE FORMER



Using range

Suitable for packing fragile bulk material with irregular shapes and requiring high measuring accuracy, such as: prawn cracker, potato chips, banana chips, crispy rice, biscuit, peanut, roasted seeds, sweets, nuts, salt, sugar, frozen food, vegetable, hardware, plastic parts accessories etc.

Optional Function:

- 1. Air flushing system
- 2. Nitrogen gas flushing
- 3. Hole punch device
- 4. Tear notch device
- 5. Link bag device
- 6. Flip device
- 7. Gusset bag
- 8. PE bag device

Optional External Device:

- 1. Air Compressor
- 2. Check weigher
- 3. Metal detector
- 4. Nitrogen making machine
- 5. 14 head combined weigher
- 6. Sala combined weigher



Four weighers



Semi-automatic vertical type